L/GHTCORP

PIPER

Piper delivers color temperature control unlike any other. Comprised of a three-step soft touch dimming interface and selectable color temperature ranging from 2700K – 6500K, it provides a spectrum of illumination from warm to cool—providing the perfect light from day to night. An integrated USB port is housed in its base, making for readily-accessible electronic charging. A manual timer allows you to set a 50-minute automatic shut-off to conserve energy use.

Finish			
--------	--	--	--

۱۸/	hit	to	





PIPER

Features

- Color temperature changeability
- Programmable shut-off timer after 50 minutes
- 3-step dimming from 100% to 63% to 30%
- USB charging port built into base

Specifications

Power consumption: Color temperatures: Luminosity: Color rendering index: Rated lifespan: Number of LEDs: Cord: USB Charge Port: 9.5 system watts 2700K/4500K/6000K 511 lumens 82 CRI > 30,000 hours 36 fractional LEDs 5' white 5V, 1A max., Type A

Sustainability Notes

- Made with fully-recyclable aluminum and plastic
- Energy-saving features such as programmable shut-off and dimming
- Lower power consumption
- Mercury-free
- Potential LEED points: Interior Lighting (possible 2 points), Interior Lighting Controls (possible 1 point).
 For more LEED information please visit https://new.usgbc.org/leed-v41

Certifications



ETL listed: compliant to UL 153 & CSA C22.2 No. 250.4; FCC Part 15 Class B; TAA

Warranty

The Piper fixture is warranted for a period of 3 years.

Dimensions



Photometric Data

Footcandle output measured at 15" from the work surface at 6500K.

	18"	12"	6"	CL	6"	12"	18"
12"	10	20	34	43	34	19	9
6"	14	33	69	95	66	31	13
CL	16	40	92	130	87	37	15
6"	14	32	67	89	63	30	13
12"	9	19	33	43 95 130 89 45	31	18	9

L/GHTCORP 17619.000.000 Rev D